



KOYO BEARING LIMITED



3.937 Inch | 100 Millimeter x 7.087 Inch | 180 Millimeter x 1.811 Inch | 46 Millimeter SKF NU 2220 ECP/C3 Cylindrical Roller Bearings

Bearing No. NU 2220 ECP/C3

NU 2220 ECP/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.824
EAN	7316577031891
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	100MM Bore; Straight Bore Profile; 180MM Outside Diameter; 46MM Width;



KOYO BEARING LIMITED

	Polymer Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose In
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 2220 ECP/C3
Weight / LBS	10.626
d	3.937 Inch 100 Millimeter
D	7.087 Inch 180 Millimeter
B	1.811 Inch 46 Millimeter
bore diameter:	100 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	180 mm
maximum rpm:	4550 RPM
overall width:	46 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	46 mm



KOYO BEARING LIMITED

operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	380 kN
series:	NU22
static load capacity:	450 kN